



Koyker Manufacturing Company
 200 N. Cleveland, P.O. Box 409
 Lennox, SD 57039

1-800-456-1107
 www.koykermfg.com

2585 Pro Loader

A Universal Loader That Fits A Variety of Tractors

DESCRIPTION OF EQUIPMENT RATED

Loader Model	Koyker Pro 2585
Bucket	679236
Width (inches)	8' 1"
Depth (inches)	2' 7"
Height (inches)	2' 8"
Length (inches)	3' 5"
Bucket Weight (pounds)	850
Capacity	37 ft ³
Bucket Control	Dual
Tractor Model	DNA
Tires	DNA
Wheelbase	DNA
Hydraulic System	DNA
Rated Flow	25 GPM
Maximum Pressure	2560
Lift Cylinder Dia. (inches)	3 1/4
Attachment Dia. (inches)	3 1/4
Tractor HP Range	90-180

Dimensional Specifications

Lift Height	13' 9"
Lift Height under level bucket	12' 11"
Clearance with bucket dumped	10' 8"
Reach at max. lift height	DNA
Max. dump angle	46
Reach with bucket on ground	DNA
Max. rollback angle	34
Digging depth	7"
Overall height in carry position	7' 2"
Mount height	5' 3"

Operational Specifications

Lift Capacity to max. ht. @ pivot pin	5015
Lift capacity to max. height (31.5)	3491
Lift capacity to max. height (19.7)	DNA
Lift capacity to 59" ht. @ pivot pin	6055
Lift capacity to 59" height (31.5)	4727
Breakout force @ pivot pin	6776
Breakout force	5039
Bucket rollback force @ maximum ht.	7424
Bucket rollback force @ 59" lift ht.	10834
Bucket rollback force @ ground line	4624
Raising Time	4.8
Lowering Time	3.4
Bucket Dumping Time	4.2
Bucket Rollback Time	3



FEATURES

- Mechanical Self-Leveling
- Euro Attachment System
- Uni-Seal Pistons
- Greaseless
- Increased Roll Back Angle & Force
- Soft Ride Nitrogen Accumulator