



1. BAG ROLLER

Hydraulically driven, **16 foot wide bag roller** for precise control and ample room for bags as they are emptied.

2. MAIN AUGER

With a **17 inch diameter main auger** made of 1/4 inch flighting, the auger can transfer **8500 bushels per hour**. The 50 degree angle provides ample height clearance for taller trucks and grain carts.

3. CROSS AUGER

Powerful **10 inch diameter cross augers** are driven from the outside end by a drive shaft and chain. Designed for unrestricted high-flow performance.

4. BAG KNIFE

Position and secure the bag knife for operation or storage in seconds. Two cutting positions ensure a positive cut through any shape bag.

5. 3RD WHEEL- (OPTIONAL)

Give your whole rig additional support when ground conditions are soft or questionable with a bolt on third wheel.

6. 9' CROSS AUGER- (OPTIONAL)

For use with 9' diameter storage bags, the unloader will require the optional 9' short cross auger to be installed.

- Folding auger retracts and extends hydraulically.
- Heavy duty auger hinge point & coupling points.
- Single person operation.
- Shear bolt protected drive train.
- Easy to use operator controls.
- Hydraulically controlled bag roller drive.
- Safe bag removal clutch.
- High speed, massive capacity, long life.



**GETTING YOUR
PRODUCT
QUICKLY
OUT OF THE
BAG AND TO
MARKET!**

FLEXSTOR 1060 GRAIN UNLOADER



BRING GRAIN BAG STORAGE OPERATION FULL CIRCLE