

1-800-557-4689 • www.koykermfg.com

1-605-336-1750 • 200 N Cleveland • Lennox, SD 57039





LEGEND SERIES FARM EQUIPMENT

EQUIPMENT FOR YOUR CURRENT FARM MACHINERY

All Legend Equipment Is:

BUILT TO LAST

Each part of the Legend Equipment series is professionally engineered. Products are built to always meet and/or exceed OEM standards. When it comes to quality products, we know how to do it right from the beginning.

AVAILABLE WITH MANY OPTIONS

From self-leveling to non self-leveling loader options, Legend Equipment has the products you need, including loader attachments and accessories.



Dealer Network

Legend Equipment is available at a number of dealerships nationwide. A complete list of dealers is available by visiting www.koykermfg.com or by contacting one of our friendly customer service staff.

Customer Service

Monday - Friday, 8am to 5pm CST. 1-800-557-4689 • 1-605-336-1750



Visit our website **www.koykermfg.com** by scanning this QR code with your smartphone.

History

Located in Lennox, SD, just 20 miles south of Sioux Falls, Legend Equipment is an innovative leader, engineering it's products to offer the latest in design and efficiency.

The people at Legend Equipment take great pride in offering quality products to our customers. "We don't just want our customers to be satisfied.... we want them to be *delighted* to do business with us!"

Scott Rysdon, CEO & President of Legend Equipment

Leading Equipment Manufacturer













542 LEGEND LOADER

Maximum Lift Height Digging Depth 7" Roll-back Angle At Ground 32° Dump Angle At Max Height Reach At Ground Level Lift Capacity Max. Height at Pivot Pin 2,500 lbs.	LOADER FEATURES	Non Self Leveling
Roll-back Angle At Ground 32° Dump Angle At Max Height 70° Reach At Ground Level Lift Capacity Max. Height at Pivot Pin 2,500 lbs.	Maximum Lift Height	10′6″
Dump Angle At Max Height Reach At Ground Level Lift Capacity Max. Height at Pivot Pin 2,500 lbs.	Digging Depth	7″
Reach At Ground Level 5′ 11″ Lift Capacity Max. Height at Pivot Pin 2,500 lbs.	Roll-back Angle At Ground	32°
Lift Capacity Max. Height at Pivot Pin 2,500 lbs.	Dump Angle At Max Height	70°
at Pivot Pin 2,500 lbs.	Reach At Ground Level	5′11″
		2,500 lbs.
Breakout Force at Ground Line at Pivot Pin (2500psi) 3,484 lbs.	Breakout Force at Ground Line at Pivot Pin (2500psi)	3,484 lbs.

40-90 HP JD Tractors

Mounted with the Legend 542 loader

5103 5105 5200 5203	5303 5310 5320 5325	5500 5510 5520 5525	5055E 5065E 5075E 5083E	5065M 5075M 5085M	5095M 5105M
5205	5400	5603	5093E		
5210	5403	5625	5101E		
5220	5410	5045E			
5225	5420			/ No	HE III I
5300	5425				

Optional Plumbing Kit Available

Valve is mounted under the tractor with the joystick mounted on a convenient stand in the cab for easy operator use.

542 Features/Benefits

Meets or exceeds OEM standards

- 6' and 7' bucket sizes available
- · Quick attach mounting
- Self-storing parking stands Solid knee joint strength
- · Easy on/off attachments
- · Fast attaching buckets
- Skid steer & 500 series compatible
- · Grade 50 steel







Parts Are Interchangeable With JD Parts

The 542 Loader fits a number of JD series tractors. Optional plumbing kit available. Specifications are subject to change without notice. JD is a registered trademark of the John Deere Corporation.

1-800-557-4689

www.koykermfg.com • 1-800-557-4689





640 LEGEND LOADERS		
LOADER FEATURES	Non Self Leveling	Self Leveling
Maximum Lift Height	12′2″	12′2″
Digging Depth	7″	7"
Roll-back Angle At Ground	15°	38°
Dump Angle At Max Height	39°	80°
Reach At Ground Level	8′	8′
Lift Capacity Max. Height at Pivot Pin	3,300 lbs.	3,410 lbs.
Breakout Force at Ground Line at Pivot Pin (2500psi)	5,800 lbs.	5,890 lbs.

55-100 HP JD Tractors

Mounted with the Legend 640 loader

6000 Series:



Optional Plumbing Kit Available

Valve is mounted under the tractor with the joystick mounted on a convenient stand in the cab for easy operator use.

640 Features/Benefits

Meets or exceeds OEM standards

- 7' and 8' bucket sizes available
- · Quick attach mounting
- Self-storing parking stands Solid knee joint strength
- Easy on/off attachments
- Fast attaching buckets
- Global & 600/700 series compatible
- · Grade 50 steel







Parts Are Interchangeable With JD Parts

The 640 Loader fits a number of JD series tractors. Optional plumbing kit available. Specifications are subject to change without notice. JD is a registered trademark of the John Deere Corporation.



80-135 HP JD Tractors

Mounted with the Legend 675 loader

- 6105M 6115M 6125M
- 6105R 6115R 6125R
- 6130 6230 6330 6430 Premium

675 Base Model Includes

Non self leveling loader model

- · Depth control indicator.
- Two 2 ¾"bucket cylinders.
- Two 3" lift cylinders Euro/Global bucket adapter.
- · Greaseless loader with optional soft ride.
- Third function line sets are complete with a single function hydraulic multi-coupler.

675 Features/Benefits

Greaseless

Greaseless chrome pins & nylatron bushings. No maintenance required with a proven track record of providing extended life with minimum wear.

Bucket Linkage

Provides greater bucket roll-back angle and force.

• 12'10" Lift Height

Allows selected 4 and 6 Cylinder tractors to load two layers of round bales on a semi-trailer.

Lower Torque Tube

Allows for greater hood clearance and clearance of larger weight receivers.

Machined Cylinder End Caps

Provides added strength and durability over welded.

675 | FGFND | OADER

0/3 LLGLND LONDLN		
LOADER FEATURES	Non Self Leveling	
Maximum Lift Height	12′10″	
Digging Depth	7″	
Roll-back Angle At Ground	30°	
Dump Angle At Max Height	46°	
Reach At Ground Level	N/A	
Lift Capacity Max. Height at Pivot Pin	4,200 lbs.	
Lift Capacity Max. Height at 31.5" Forward of Pivot Pin	2,900 lbs.	
Breakout Force at Ground Line at Pivot Pin (2500psi)	5,380 lbs.	
Breakout Force at Ground Line 31.5" Forward of Pivot Pin:	4,030 lbs.	

Soft Ride Option

Removes the shock loading on the loader, loader mounts, tractor and operator, longer life of the loader/tractor and less operator fatigue. Soft Ride option includes hydraulic hook up from the loader to the tractor valve and contains the loader half of the multi-coupler that matches to the factory coupler.

675 Legend Loader

Compatible only with JD tractor models listed that are equipped with JD H310-H340 loader ready mounts, factory controls, valve and tractor half of the three function hydraulic multi-coupler. Specifications are subject to change without notice. JD is a registered trademark of the John Deere Corporation.

1-800-557-4689

www.koykermfg.com • 1-800-557-4689





740 LEGEND LOADERS			
LOADER FEATURES	Non Self Leveling	Self Leveling	
Maximum Lift Height	13′8″	14′1″	
Digging Depth	10″	12"	
Roll-back Angle At Ground	29°	40°	
Dump Angle At Max Height	45°	70°	
Reach At Ground Level	8′2″	8′2″	
Lift Capacity Max. Height at Pivot Pin	4,193 lbs.	4,083 lbs.	
Breakout Force at Ground Line at Pivot Pin (2500psi)	8,171 lbs.	7,647 lbs.	

100-174 HP JD Tractors

Mounted with the Legend 740 loader

		9				
2940	4050	4455	7320	7420	7610	
2950	4055	4630	7330	7430	7700	
2955	4230	6605	7400	7510	7710	
3055	4240	6615	7405	7520	7800	
3130	4250	6715	7410	7600	7810	
3140	4255	7130				
3150	4350	7200				
3155	4430	7210			1	-
		_				
3255	4440	7220	660	77		
4040	4450	7230			-	
						-
						100
					7	
			100	5/M/		
	THE CALL	1 100				-0
			-5'	1500	1	
	· \		9			
	A CONTRACTOR OF THE PARTY OF TH		## \ \ \			
alaska .						W.
	11	0			1	(A)
116	100	11			1. 1	
An		76		- 2	The same	4/10
	A.	VI SE				
	1	1,	16 "			

740 Features/Benefits

Meets or exceeds OEM standards

- 7', 8' and 8' 6" bucket sizes available
- · Quick attach mounting
- · Self-storing parking stands · Grade 50 steel
- Euro/Global and 600/700 series quick attachments
- Solid knee joint strength







Parts Are Interchangeable With JD Parts

The 740 Loader fits a number of JD series tractors. Optional plumbing kit available. Specifications are subject to change without notice. JD is a registered trademark of the John Deere Corporation.







780 LEGEND LOADERS Non Self Self **LOADER FEATURES** Leveling Leveling Maximum Lift Height 13'5" 13'5" Digging Depth 7.5" 7.5" Roll-back Angle At Ground 36° 36° 48° 48° Dump Angle At Max Height Reach At Ground Level N/A N/A Lift Capacity Max. Height at Pivot Pin 5,216 lbs. 5,067 lbs. Lift Capacity Max. Height at 31.5" Forward of Pivot Pin 3,607 lbs. 3,527 lbs. Breakout Force at Ground Line at 5,757 lbs. 6,802 lbs. Pivot Pin (2500psi) Breakout Force at Ground Line 31.5" 4,500 lbs. 5,059 lbs. Forward of Pivot Pin:

90-180 HP JD Tractors

Mounted with the Legend 780 loader

- 6140M 6150M 6170M
- 6140R 6150R 6170R 6190R 6210R
- 7130 7230 7330 7430 7530 Premium

780 Base Model Includes

Available in NSL and SL models

- Bucket level indicator.
- Two 3 ¼" bucket cylinders.
- Two 3 ¼" lift cylinders and Euro/Global bucket adaptor.
- · Greaseless loader with optional soft ride.
- SL model features mechanical self-leveling.

780 Features/Benefits

- 7', 8' and 8' 6" bucket sizes available
- · Quick attach mounting
- Accepts Euro/Global attachments
- · Easy on/off attachments
- Self-storing parking stands
- Solid knee joint strength
- · Grade 50 steel
- Greaseless
- · Bucket linkage
- · Handles big loads easily
- Soft ride option including hydraulic hook up

Optional Soft Ride Feature

The optional feature of adding the soft ride nitrogen accumulator feature creates an easy-riding environment. This environment makes it easier on the mount, the loader, the tractor and YOU!

780 Legend Loader

Compatible only with JD tractor models listed that are equipped with JD H360-H380 loader ready mounts, factory controls, valve and tractor half of the three function hydraulic multi-coupler.

Specifications are subject to change without notice. JD is a registered trademark of the John Deere Corporation.

Attachments Bale Spears, Pallet Forks & Grapples



- Singles Have 2200 LBS Capacity
- Tapered Socket Provides Support For Spear



- Doubles Have 4400 LBS Capacity
- Standard 4 Tine Square Bale Spear Has The Option 39" or 48" Tines



- · Fast On-Off System
- Fully Tapered Tines Allow For Easier Penetration and Withdrawal

All feature quick attach systems & are skid steer compatible. Euro/Global, 600/700/500 series hookups available.























40-90 HP JD Tractors 5103 5400 5403 5410 3,484 LBS 5105 5055E 5200 5065E Breakout Force @ Pivot Pin 5075E 5203 5205 5420 5083E 5210 5425 5093E 5220 5500 5101E 2,500 LBS 5225 5300 5520 5075M Lift Capacity to 5303 5525 5085M Full Height at Pivot Pin 5310 5320 5603 5625 5095M 5105M

55-100 HP JD Tractors			
	6000 Seri	es:	
5,800 LBS	6110	6220	6400
	6120	6230	6405
Breakout Force @ Pivot Pin	6130	6300	6410
	6200	6310	6415
	6210	6320	6420
3,300 LBS Lift Capacity to Full Height at Pivot Pin	6215	6330	6430

55-100 HP JD Tractors

5,890 LBS
Breakout Force @ Pivot Pin

3,410 LBS
Lift Capacity to
Full Height at Pivot Pin

6000 Series:			
6110	6220	6400	
6120	6230	6405	
6130	6300	6410	
6200	6310	6415	
6210	6320	6420	

6330

6430

6215

80-135 HP JD Tractors

5,380 LBS
Breakout Force @ Pivot Pin

4,200 LBS
Lift Capacity to

Full Height at Pivot Pin

6105M	6105R	6130
6115M	6115R	6230
6125M	6125R	6330
		6430

Compatible only with JD tractor models listed that are equipped with JD H310-H340 loader ready mounts, factory controls, valve and tractor half of the three function bydraulic multi-coupler

1-855-LEG-EQUI

www.legendequip.com • 1-855-534-3784



100-174 HP JD Tractors 2950 4240 7510 2955 4250 Breakout Force @ Pivot Pin 3130 7610 3140 3150 4,193 LBS Lift Capacity to 4040 4630 7405 4050 4055 Full Height at Pivot Pin



100-174 HP JD Tractors

7,647 LBS
Breakout Force @ Pivot Pin

4,083 LBS
Lift Capacity to
Full Height at Pivot Pin

2940	4230	6715	7430
2950	4240	7130	7510
2955	4250	7200	7520
3055	4255	7210	7600
3130	4350	7220	7610
3140	4430	7230	7700
3150	4440	7320	7710
3155	4450	7330	7800
3255	4455	7400	7810
4040	4630	7405	
4050	6605	7410	
4055	6615	7420	



90-180 HP JD Tractors

5,757 LBS
Breakout Force @ Pivot Pin

5,216 LBS
Lift Capacity to
Full Height at Pivot Pin

6140M 6150M 6170M	6140R 6150R 6170R 6190R	7130 7230 7330 7430
	6210R	7530

The Legend 780 is compatible only with JD tractor models listed that are equipped with JD H360-H380 loader ready mounts, factory controls, valve and tractor half of the three function hydraulic multi-coupler.

130 PEGEND
780 Self Leveling Loader
13'5" Maximum Lift Height7.5" Digging Depth

90-180 HP JD Tractors

6,802 LBSBreakout Force @ Pivot Pin

5,067 LBS
Lift Capacity to
Full Height at Pivot Pin

6140M	6140R	7130
6150M	6150R	7230
6170M	6170R	7330
	6190R	7430
	6210R	7530

The Legend 780 is compatible only with JD tractor models listed that are equipped with JD H360-H380 loader ready mounts, factory controls, valve and tractor half of the three function hydraulic multi-coupler.



1-800-557-4689 • www.koykermfg.com

1-605-336-1750 • 200 N Cleveland • Lennox, SD 57039

