



**SAFEGRAIN**

# RADARMAX PLUS








**CONTINUOUS RADAR LEVEL MONITORING**



**MONITOR YOUR PRODUCT ANYTIME, ANYWHERE!**

With its advanced high-frequency signal, RadarMax Plus excels in penetrating through dust and vapor, ensuring dependable and cost-effective solution for all your grain level monitoring.

## RADARMAX PLUS IN ACTION

-  Measures distances up to 180 feet
-  Advanced non-contact, high-precision, affordable radar level sensor
-  Includes 10° adjustable swivel flange. 30° angled standpipe available
-  Standard 4-20mA and RS-485 Modbus RTU dual output
-  Includes programming and display "puck"
-  "Dust-Tight" enclosure for Class II, Div. 2 hazardous locations. UL Rated NEMA: 3S, 4X, 12, 13 and IP-68
-  RadarTrack PC Software option provides advanced features: Remote Viewing on Android, iPhone and web browsers. Automatic alerts via text message, email and output relays. Time-to-empty, reporting and graphing for inventory tracking

 **800-557-4689**

 **www.siouxsteel.com**





# RADARMAX PLUS

CONTINUOUS RADAR LEVEL MONITORING SYSTEM



**MONITOR YOUR PRODUCT ANYTIME, ANYWHERE!**

With its advanced high-frequency signal, RadarMax Plus excels in penetrating through dust, and vapor, ensuring dependable and cost-effective solution for all your grain level monitoring.

## RADARMAX PLUS IN ACTION

**Measurement Range:**  
1' (.3m) to 180 Feet (55m)

**Supply Voltage:**  
10-28 VDC

**Operating Frequency:**  
80 GHz, 6° beam

**Swivel/Tilt Flange**  
Included 10° Swivel

**Output:**  
4-20mA

**30° Mounting Flange:**  
Optional

**Communications:**  
Included Modbus  
ASCII/RTU

**Configuration Method:**  
Included Display  
Keypad

**Wireless Data:**  
Wireless Ready

**Enclosure Material:**  
AL, SS

**RadarTrack Software**  
Support

**Approval:**  
IP67, NEMA 3S: CII Div2

800-557-4689

[www.siouxsteel.com](http://www.siouxsteel.com)

